



Secured by Design Rehau Window Technical Information

IDM Doors Ltd Data Sheet 13

GENERAL

- Full range of Window styles available, white or foiled Upvc.
- Manufactured from 70mm Pvc-U Synseal Legend 70 - 70mm profile suite.
- Low maintenance and high performance.

Hardware

- Mila 8 series shootbolt espagnolette locking system in stainless steel.
- Mila Proliner key locking lever handle (cranked).
- Cotswold restrictor hinge HS Sindex 430 stainless steel or egress hinge as required and as position of window in dwelling dictates.
- Low maintenance; wipe down with soft cloth and warm water to clean. Light lubrication to moving parts every six months.

General Specification

- Thermal reinforcements
- Warm edge spacer bars to glass units
- Cotswold glass to bathroom windows and where obscure glass required
- Trickle vents to all windows 300mm with integral fly screen
- Energy rating C as standard – Pilkington K glass and Optiwhite with thermal spacer bar and Argon gas filled cavity.
- Energy rating A also available on request, Pilkington K Soft Coat glass and Optiwhite with thermal spacer bar and Argon gas filled cavity.
- Chamfered profile to external, ovolo glazing bead to internal – windows internally beaded.

Registrations

- Fensa – Registration number 32693
- BBA – Under review
- BFRC Authorised Retailer Scheme – under review